



### A wise and affordable choice

Forward compressors provide you with reliable and continual compressed air for various compressed air application and industrial demands, with its imperial rigorous design concept from Europe.

- One key start & stop: simple and stable operation
- · Intelligent control system: real-time monitoring operation status, including function of self-service reminder and fault inspection alarm, a friendly experience of human-machine interface
- · Concise layout internally: for easier maintenance and less service time










### **Cooling system**

- · Extra large surface cooler, allow maximum 46 °C ambient environment use
- · Thermostatic control cooling fan, efficiently prevents over-cooling and condensate





### Professional soundproof design

· Fully sealed cabinet with soundproofing and noise-reducing partitions to minimize noise





- · Latest generation design air end
- · High precision manufacturing process
- · Results to high performance compressor air delivery



### Anti-leakage connection of pipes

· Hose and hard tube connection, with high temperature & pressure resistant hose and O rings, a fully rigid and stable structure design



#### Intelligent controller

- · One key press to switch on/off
- · Self-service timing management
- · Self-protection at fault: auto-stop and check, instant alarm at the same time



### **Pre-filtering**


- · Allows the maximum volume air inlet at the minimum pressure drop
- · Slot design enables quick removal for reguler cleaning



## FCA technical data

Model	Pressure	Motor		Capacity			Noise	Weight	Connection
	Мра	Нр	kW	l/s	cfm	m³/min	dB±2	KG	G
FCA 4	0.8	5.5	4	9	18	0.51	66	130	1/2
	1			8	16	0.46			
	0.8	7.5	5.5	13	28	0.8	66	160	1/2
FCA 5.5	1			11	23	0.65			
FCA 7.5	0.8	10	7.5	18	37	1.05	66	167	1/2
FCA 7.5	1			14	30	0.85			
ECA 44	0.8	15	11	27	58	1.6	72	231	3/4
FCA 11	1.0			23	48	1.4			
FCA 15	0.8	20	15	33	70	2.0	73	242	3/4
FCA 15	1.0			31	65	1.8			
	0.8	25	18.5	49	103	2.9	72	330	1
FCA 18.5	1.0			41	87	2.5			
ECA 22	0.8	30	22	55	117	3.3	72	350	1
FCA 22	1.0			46	98	2.8			
	0.7	40	30	82	174	4.9	79	490	1.5
FCA 30	0.8			78	166	4.7			
	1.0			63	132	3.8			
	0.7	50	37	97	204	5.8	79	524	1.5
FCA 37	0.8			95	201	5.7			
	1.0			83	176	5.0			
FCA 7.5 FF	0.8	10	7.5	18	37	1.05	66	358	1/2
FCA 7.5 FF	1			14	30	0.85			
ECA 44 EE	0.8	15	11	27	58	1.6	72	430	1
FCA 11 FF	1.0			23	48	1.4			
FCA 15 FF	0.8	20	15	33	70	2.0	73	430	1
FCA 15 FF	1.0			31	65	1.8			

	Dimension						
Model	Length mm	Width mm	Height mm				
FCA 4	650	650	890				
FCA 5.5	650	650	890				
FCA 7.5	650	650	890				
FCA 11	850	650	930				
FCA 15	850	650	930				
FCA 18.5	710	740	1275				
FCA 22	710	840	1275				
FCA 30	860	850	1345				
FCA 37	860	850	1345				
FCA 7.5 FF	1547	650	1475				
FCA 11 FF	1537	650	1430				
FCA 15 FF	1537	650	1430				



















# Care. Trust. Efficiency.

### Care.

Care is what service is all about: professional service by knowledgeable people, using high-quality original parts.

### Trust.

Trust is earned by delivering on our promises of reliable, uninterrupted performance and long equipment lifetime.

### Efficiency.

Equipment efficiency is ensured by regular maintenance. Efficiency of the service organization is how Original Parts and Service make the difference.

### **Forward Compressors**

U 12 / 8 Baretta Road Wangara, WA, 6065 t: 08 9409 9623

w: forwardcompressors.com.au